



SPECIFICATIONS

| | |
|--------------------------------|---|
| Description: | Full-range in-room loudspeaker |
| Tweeter: | Air Motion Transformer, Kapton foil, Neodymium magnet |
| Midrange: | 165mm / 6,5", anodized aluminum cone, vented magnet with copper clad pole piece, 35mm / 1,4" two-layer voice coil, molded aluminum basket |
| Woofer: | Two 30 cm / 12", anodized aluminum cone, vented double magnet with copper ring, 75mm / 3" four-layer voice coil, molded aluminum basket |
| Enclosure: | Closed cabinet, aluminum and MDF, steel base |
| Frequency range: | 25 – 22,000 Hz (-3 dB) |
| Amplification: | A1 or A2 Amplifier, 2 x 400 watt per loudspeaker |
| Amplification channels: | 2 per loudspeaker |
| Max SPL@1m: | 114 dB |
| Crossover: | Woofer/Midrange: Digital crossover stored in processor, 200 Hz. Midrange/Tweeter: Passive crossover, 2200Hz |
| Connections: | Neutrik speakON |
| Placement: | Floor-standing, against the wall |
| Dimensions (W x H x D): | 500 x 1150 x 270 mm / 19,7 x 45,3 x 10,6 inches (incl. base plinth) |
| Weight: | 76 kg / 168 lb |
| Finish: | Black piano finish, custom finishes available |